

**Table 1: Technical specifications of the equipment**

Table 1: Technical specifications of the equipment:

Capacity	500L
Capacity (L)	500
Capacity (L) (with 22.5 L of water)	22.5
Capacity (L) (with 1.1 L of water)	1.1
Capacity (L) (with 5 L of water)	5
Capacity (L) (with 2.5 L of water)	2.5
Capacity (L)	515
Capacity (L) (with 1035 * 1480 mm)	Φ1035 * 1480

Table 1:

Table 1: Technical specifications of the equipment. The table shows the capacity of the equipment in liters (L) for different configurations. The capacity is 500L for the standard configuration, 22.5L for the configuration with 22.5L of water, 1.1L for the configuration with 1.1L of water, 5L for the configuration with 5L of water, 2.5L for the configuration with 2.5L of water, 515L for the configuration with 515L of water, and Φ1035 \* 1480 for the configuration with 1035 \* 1480 mm.

Table 1: Technical specifications of the equipment & equipment

Table 1: Technical specifications of the equipment. The table shows the capacity of the equipment in liters (L) for different configurations. The capacity is 500L for the standard configuration, 22.5L for the configuration with 22.5L of water, 1.1L for the configuration with 1.1L of water, 5L for the configuration with 5L of water, 2.5L for the configuration with 2.5L of water, 515L for the configuration with 515L of water, and Φ1035 \* 1480 for the configuration with 1035 \* 1480 mm.

Table 1:

1. The table shows the capacity of the equipment in liters (L) for different configurations. The capacity is 500L for the standard configuration, 22.5L for the configuration with 22.5L of water, 1.1L for the configuration with 1.1L of water, 5L for the configuration with 5L of water, 2.5L for the configuration with 2.5L of water, 515L for the configuration with 515L of water, and Φ1035 \* 1480 for the configuration with 1035 \* 1480 mm.

2. The table shows the capacity of the equipment in liters (L) for different configurations. The capacity is 500L for the standard configuration, 22.5L for the configuration with 22.5L of water, 1.1L for the configuration with 1.1L of water, 5L for the configuration with 5L of water, 2.5L for the configuration with 2.5L of water, 515L for the configuration with 515L of water, and Φ1035 \* 1480 for the configuration with 1035 \* 1480 mm.

Table 1:



**Yes, we can! Ok, we do!**  
**Quality, we promise!**



<http://www.aemost.com/>

**CE ISO**

□□□□□□□□ □□□□□□:



□□□□:







□□□□□□□□:



# CERTIFICATES FOR QUALITY ASSURANCE



Equipment variety complete, reasonable price !

Excellent quality assurance, customer service !

□□□□□□ □□□□□:

