

Table Specifications:

Table	600
Wiremesh & amp; ; (mm)	600
Wiremesh & amp; ; (mm / mm)	1-6
Table (mm)	3
Table (mm)	14
Table (mm)	2-10
Table (mm)	16.5
Table (mm)	2300
Table (mm)	17500 * 950 * 1800

Enrobing Specifications:

Enrobing is the process of applying a protective layer of material to the surface of a concrete structure. This process is used to prevent the concrete from being damaged by environmental factors such as moisture, salt, and acid rain. The enrobing material is applied in a layer that is typically 1-6 mm thick. The enrobing material is applied to the surface of the concrete structure in a zigzag pattern. The enrobing material is applied to the surface of the concrete structure in a zigzag pattern.

1. Enrobing is applied to the surface of the concrete structure in a zigzag pattern.
2. Enrobing is applied to the surface of the concrete structure in a zigzag pattern.
3. Enrobing is applied to the surface of the concrete structure in a zigzag pattern.

Enrobing & amp; ; Specifications:

1. Enrobing is applied to the surface of the concrete structure in a zigzag pattern.
2. Enrobing is applied to the surface of the concrete structure in a zigzag pattern.

Table:

Table 1., Enrobing is applied to the surface of the concrete structure in a zigzag pattern.

2. Enrobing is applied to the surface of the concrete structure in a zigzag pattern.

Table Specifications:



□□□□□□:



□□□□□□□□□□:

**CERTIFICATES FOR QUALITY ASSURANCE**

<p>CE</p> 	<p>CE</p> 	<p>Patent Certificate</p> 	<p>ISO</p> 	<p>ISO</p> 
Equipment variety complete, reasonable price !		Excellent quality assurance, customer service !		

□□□□ □□ □□□□□□□□:

