

Technical Specifications

Weight	1200
Weight (with accessories)	1200
Dimensions (mm / inches)	1 ~ 6
Depth (mm)	5
Width (mm)	22
Height (mm) (without display)	2 ~ 10
Height (mm) (with display)	28.5
Volume (mm)	4050
Dimensions (mm)	25500 * 1450 * 1800

Installation:

Installation instructions: Please refer to the user manual for detailed information on how to install the device. The device is designed to be installed in a standard 19-inch rack.

1. Installation location: The device should be installed in a well-ventilated area to ensure proper airflow and cooling.
2. Power requirements: The device requires a power source with a voltage range of 100V to 240V AC and a frequency of 50/60 Hz.
3. Safety precautions: Before installation, please ensure that the power is disconnected. Use appropriate safety measures when handling the device.

Power consumption: amp;

1. The power consumption of the device is approximately 1.5A at 100V AC.
2. The power consumption of the device is approximately 3.6A at 240V AC.

Dimensions:

1. The dimensions of the device are 255mm (W) x 145mm (D) x 180mm (H).

2. The dimensions of the device are 255mm (W) x 145mm (D) x 180mm (H).





□□□□□□:



**SUZHOU ASIA-EUROPE BRIDGE
ELECTRONIC TECHNOLOGY CO., LTD.**

□□□□□□:

CERTIFICATES FOR QUALITY ASSURANCE

<p>CE</p> 	<p>CE</p> 	<p>Patent Certificate</p> 	<p>ISO</p> 	<p>ISO</p> 
<p>Equipment variety complete, reasonable price !</p>			<p>Excellent quality assurance, customer service !</p>	

□□□□□□ □□ □□ □□□□□□:

