

Table Specifications:

Model	YOQ-E250
Wiremesh Size (mm)	250
Wiremesh Thickness (mm / inch)	3.5-6.5
Refrigeration Capacity	1 ton
(Cooling Capacity (kW))	5
(Cooling Capacity (BTU/hr))	2-15
Weight (kg)	10.94
Dimensions (mm)	840 * 940 * 1780

Installation:

Enrobing is a process of applying a protective coating to the surface of a pipe or cable. This process is used to protect the underlying material from environmental factors such as corrosion, abrasion, and chemical damage.

The following steps describe the enrobing process:

1. **Preparation:** Enrobing is performed on a pipe or cable that has been cleaned and prepared for coating.
2. **Enrobing:** Enrobing is performed by applying a coating material to the surface of the pipe or cable.
3. **Post-Enrobing:** Enrobing is performed using a zigzag pattern to ensure uniform coverage.

The 250mm Enrobing is performed using a coating material that is applied to the surface of the pipe or cable. The coating material is applied in a zigzag pattern to ensure uniform coverage. The Omron is used to control the enrobing process.

& amp; Installation:

1. The pipe or cable is prepared for enrobing.
2. The enrobing process is performed using a zigzag pattern.

Notes:

1. The enrobing process is performed using a zigzag pattern to ensure uniform coverage.

2. The enrobing process is performed using a zigzag pattern to ensure uniform coverage.

Notes:









□□□□□ □□□□□□□□:



□□□□□□:





□□□□□□□□:

4 Certificates 

CERTIFICATES FOR QUALITY ASSURANCE

<p>CE</p>  <p>Equipment variety complete, reasonable price !</p>	<p>CE</p> 	<p>Patent Certificate</p> 	<p>ISO</p>  <p>Excellent quality assurance, customer service !</p>	<p>ISO</p> 
--	--	--	---	---

□□□□□□ □□ □□□□:

