

**Dimensions (mm):**

Height	600
Panel width (mm)	600
Panel depth (mm)	32
Panel weight (kg)	0.75
Panel thickness (mm)	60
Panel length (mm)	500 × 2
Panel area (mm <sup>2</sup> )	15
Panel volume (mm <sup>3</sup> )	* 700 * 1100 700
Panel weight (kg)	120

**Notes:**

Dimensions are approximate. All dimensions are given in millimeters (mm). The panel is made of **colorized aluminized** material. The panel is available in different colors and finishes. The panel is suitable for use in indoor and outdoor environments. The panel is suitable for use in a wide range of applications. The panel is suitable for use in a wide range of applications.

**Installation & Maintenance:**

- 1. The panel should be installed in a dry, clean environment.
- 2. The panel should be installed in a dry, clean environment.

**Caution:**

Do not touch the panel with bare hands. Use gloves when handling the panel. Do not use harsh cleaning agents or abrasive materials. Do not use high pressure water cleaning.

- 2. Do not use the panel in a wet or humid environment. Do not use the panel in a high temperature environment. Do not use the panel in a low temperature environment. Do not use the panel in a high humidity environment. Do not use the panel in a low humidity environment.

**Other Information:**



□□□□□□:

□□□□□□□□:

# CERTIFICATES FOR QUALITY ASSURANCE

**CE**



China Quality Certification Centre  
CERTIFICATE OF CONFORMITY

**CE**



ITS INSPECTION & CERTIFICATION CO., LIMITED  
CERTIFICATE OF CONFORMITY

**Patent Certificate**



实用新型专利证书

**ISO**



CERTIFICATE  
Sulphur ShanghaiChina Certification Center

**ISO**



ZOHY  
QUALITY MANAGEMENT SYSTEM  
CERTIFICATE

Equipment variety complete, reasonable price !

Excellent quality assurance, customer service !

□□□□ □□ □□□□□□□□:

