

Table Specifications:

Model	YOQ-E250
Wiremesh Size (mm)	250
Wiremesh Thickness (mm / inch)	3.5-6.5
Refrigeration Capacity	1 ton
(Refrigerant Type)	5
(Refrigerant Temperature °C)	2-15
Weight (kg)	10.94
Dimensions (mm)	8400 * 940 * 1780

Installation:

Enrobing is a process of coating a wire mesh with a material to protect it from corrosion and to improve its strength. The process involves dipping the wire mesh into a bath of molten material, which is then cooled and solidified.

The following steps describe the enrobing process:

1. **Preparation:** Enrobing is performed on a wire mesh that has been cleaned and prepared for coating.
2. **Enrobing:** Enrobing is performed by dipping the wire mesh into a bath of molten material, which is then cooled and solidified.
3. **Post-Enrobing:** Enrobing is performed by dipping the wire mesh into a bath of molten material, which is then cooled and solidified. The resulting wire mesh is then cut into sections and packaged.

The 250mm Enrobing is a process of coating a wire mesh with a material to protect it from corrosion and to improve its strength. The process involves dipping the wire mesh into a bath of molten material, which is then cooled and solidified. Omron is a brand of electrical components.

& amp; Specifications:

1. The specifications for the Enrobing process are as follows:
2. The specifications for the Enrobing process are as follows:

Notes:

1. The specifications for the Enrobing process are as follows:

2. The specifications for the Enrobing process are as follows:

Notes:









□□□□□ □□□□□□□□:



□□□□□□:





□□□□□□□□□□:

4 Certificates 

CERTIFICATES FOR QUALITY ASSURANCE

<p>CE</p>  <p>Equipment variety complete, reasonable price !</p>	<p>CE</p> 	<p>Patent Certificate</p> 	<p>ISO</p>  <p>Excellent quality assurance, customer service !</p>	<p>ISO</p> 
--	--	--	---	---

□□□□□□□□ □□ □□□□:

