

Table Specifications:

Model	YOQ-E250
Wiremesh Size (mm)	250
Wiremesh Thickness (mm / inch)	3.5-6.5
Refrigeration Capacity	1 ton
(Cooling Capacity (kW))	5
(Cooling Capacity (BTU/hr))	2-15
Weight (kg)	10.94
Dimensions (mm)	840 * 940 * 1780

Installation:

**Enrobing** is a process of applying a protective coating to the surface of a pipe or cable. This process is used to protect the underlying material from environmental factors such as corrosion, abrasion, and chemical damage.

The following steps describe the enrobing process:

1. **Preparation:** Enrobing is performed on a pipe or cable that has been cleaned and prepared for coating.
2. **Enrobing:** Enrobing is performed by passing the pipe or cable through a bath of molten material, which coats the surface.
3. **Post-Processing:** Enrobing is performed using zigzags to ensure the coating is applied evenly.

The 250mm Enrobing is performed using Omron sensors to ensure the coating is applied evenly.

**& amp;** Installation:

1. The pipe or cable is prepared for enrobing.
2. The pipe or cable is passed through the enrobing bath.

Notes:

1. The enrobing process is performed using Omron sensors to ensure the coating is applied evenly.

2. The enrobing process is performed using zigzags to ensure the coating is applied evenly.

Notes:









□□□□□ □□□□□□□□:



□□□□□□:





□□□□□□□□:

**4 Certificates** 

**CERTIFICATES FOR QUALITY ASSURANCE**

<p><b>CE</b></p>  <p>Equipment variety complete, reasonable price !</p>	<p><b>CE</b></p> 	<p><b>Patent Certificate</b></p> 	<p><b>ISO</b></p>  <p>Excellent quality assurance, customer service !</p>	<p><b>ISO</b></p> 
--	--	--	---	---

□□□□□□ □□ □□□□:

